

FT TEF-R

TECHNICAL DATA SHEET

FT TEF-R is modified Polytetrafluorethylene (PTFE) heat-shrinkable tubing with excellent resistance to chemical products.

It has a continuous working temperature of up to +260°C and can withstand peaks of up to +400°C for short periods. With a shrink ratio of 4:1, **FT TEF-R** provides long-lasting cable insulation and even improves the performances of the components it protects.

Working temperature Up to +260°C

Standard colours Clear.

Non standard colours Upon request.

DIMENSION DATA

Reference	Inside diameter (mm)		Wall-thickness after recovery (mm) (e)
	As supplied mini. (D)	After recovery maxi. (d)	
FT TEF-R 5/64"	1,98	0,63	0,23
FT TEF-R 1/8"	3,17	0,94	0,25
FT TEF-R 3/16"	4,75	1,27	0,30
FT TEF-R 1/4"	6,35	1,60	0,30
FT TEF-R 5/16"	7,92	1,98	0,30
FT TEF-R 3/8"	9,52	2,44	0,30
FT TEF-R 7/16"	11,12	2,84	0,30
FT TEF-R 1/2"	12,70	3,70	0,38
FT TEF-R 9/16"	14,27	3,94	0,38
FT TEF-R 5/8"	15,87	4,52	0,38
FT TEF-R 11/16"	17,45	5,03	0,38
FT TEF-R 3/4"	19,05	5,69	0,38
FT TEF-R 7/8"	22,22	6,20	0,38
FT TEF-R 1"	25,40	7,06	0,38
FT TEF-R 1-1/4"	31,75	8,81	0,38
FT TEF-R 1-1/2"	38,10	10,16	0,38
FT TEF-R 1-3/4"	44,45	11,43	0,38
FT TEF-R 2"	50,80	11,43	0,38
FT TEF-R 2-1/4"	57,15	14,86	0,51
FT TEF-R 2-1/2"	63,50	16,51	0,51
FT TEF-R 2-3/4"	69,85	18,03	0,51
FT TEF-R 3"	76,20	19,68	0,51
FT TEF-R 3-1/4"	82,55	21,21	0,51
FT TEF-R 3-1/2"	88,90	22,86	0,63
FT TEF-R 3-3/4"	95,25	24,38	0,63
FT TEF-R 4"	101,60	26,03	0,63

FT TEF-R

TECHNICAL CHARACTERISTICS:

Standard Requirements

PHYSICAL

Working temperature	Up to +260°C
Shrink temperature	+300°C
Shrink ratio	4 : 1

PACKAGING

1,22 m length.

FTE – FT TEF-R – 70/a - 06/04

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. Gremco shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.